


Kingtronics®**KBPC25005 THRU
KBPC2510****SINGLE-PHASE BRIDGE RECTIFIER****VOLTAGE RANGE 50 to 1000 Volts****CURRENT 25.0 Ampere****FEATURES**

High forward surge current capability.
 Low thermal resistance.
 High isolation voltage from case to lugs.
 High temperature soldering guaranteed:
 260°C/10 second, at 5 lbs. (2.3kg) tension.

MECHANICAL DATA

Case: Metal case.
 Terminal: Plated 0.25" (6.35mm) lug.
 Polarity: Polarity symbols marked on case.
 Mounting: Thru hole for #10 screw, 20 in,- lbs. Torque Max.
 Weight:1.02 ounce, 29gram.

KBPC**MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS**

Ratings at 25°C ambient temperature unless otherwise specified
Single phase, half wave, 60Hz, resistive or inductive load.
For capacitive load derate current by 20%

Dimensions in inches and (millimeters)

	SYMBOLS	KBPC 25005	KBPC 2501	KBPC 2502	KBPC 2504	KBPC 2506	KBPC 2508	KBPC 2510	UNIT
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	Volts
Maximum RMS Voltage	V_{RMS}	35	70	140	280	420	560	700	Volts
Maximum DC Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	Volts
Maximum Average Forward Rectified Output Current at $T_C=50^\circ\text{C}$ (Note1,2)	$I_{(AV)}$	25							Amps
Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I_{FSM}	300							Amps
Rating for Fusing ($t < 8.3\text{ms}$)	I^2T	373							A^2s
Maximum Instantaneous Forward Voltage at 12.5A	V_F	1.1							Volts
Maximum Reverse Current at Rated DC Blocking Voltage	I_R	$T_A=25^\circ\text{C}$							μAmps
		$T_A=125^\circ\text{C}$							mAmps
Isolation Voltage from case to lugs	V_{ISO}	2500							V_{AC}
Typical Thermal Resistance (Note 1,2)	$R_{\theta JC}$	2.0							$^\circ\text{C/W}$
Operating Temperature Range	T_J	-55 to +150							$^\circ\text{C}$
Storage Temperature Range	T_{STG}	-55 to +150							$^\circ\text{C}$

1- Unit mounted on 9"×3.5"×4.6" thick (23×9×11.8mm) Al. finned plate.

2- Bolt down on heat-sink with silicone thermal compound between bridge and mounting surface for maximum heat transfer efficiency with #10 screw.

Kingtronics® International Company

RATINGS AND CHARACTERISTIC CURVES

FIG.1-DERATING CURVE FOR
OUTPUT RECTIFIED CURRENT




FIG.2-MAXIMUM NON-REPETITIVE PEAK
FORWARD SURGE CURRENT PER ELEMENT




FIG.3-TYPICAL FORWARD CHARACTERISTICS
PER BRIDGE ELEMENT




FIG.4-TYPICAL REVERSE CHARACTERISTICS
PER BRIDGE ELEMENT




FIG.5-TYPICAL JUNCTION CAPACITANCE
PER BRIDGE ELEMENT





FIG.6-MAXIMUM POWER DISSIPATION



Note: Specifications are subject to change without notice.